

Axial Choke Valves

AT Series

ASME B16.5

Size	ASME 150		ASME 300		ASME 400		ASME 600		ASME 900		ASME 1500		ASME 2500	
	RF	RF	RTJ	RF	RTJ	RF	RTJ	RF	RTJ	RF	RTJ	RF	RTJ	
2"	292	292	295	292	295	292	295	368	371	368	371	451	454	
3"	356	356	359	356	359	356	359	381	384	470	473	578	584	
4"	432	432	435	432	435	432	435	457	460	546	549	673	683	
6"	394	403	419	495	498	559	562	610	613	705	711	914	927	
8"	457	502	518	597	600	660	664	737	740	832	841	1022	1038	
10"	533	568	584	673	676	787	791	838	841	991	1000	1270	1292	
12"	610	648	664	762	765	838	841	965	968	1130	1146	1422	1445	
14"	686	762	778	826	829	889	892	1029	1038	1257	1276	1594	-	
16"	762	838	854	902	905	991	994	1130	1140	1384	1407	1778	-	
18"	864	914	930	978	981	1092	1095	1219	1232	1527	1549	-	-	
20"	914	991	1010	1054	1060	1194	1200	1321	1334	1664	1686	-	-	
24"	1067	1143	1165	1232	1241	1397	1407	1549	1568	1937	1965	-	-	
28"	1245	1346	1372	1397	1410	1549	1562	1753	1775	-	-	-	-	
30"	1295	1397	1422	1524	1537	1651	1664	1854	1876	-	-	-	-	
32"	1372	1524	1553	1651	1667	1778	1794	1959	1981	-	-	-	-	
36"	1524	1727	1756	1880	1895	2083	2099	2165	2194	-	-	-	-	
40"	1676	1870	-	2134	-	2337	-	2375	-	-	-	-	-	
42"	1753	1956	-	2257	-	2470	-	2480	-	-	-	-	-	
48"	1981	2216	-	2623	-	2867	-	2791	-	-	-	-	-	

Face-to-Face dimensions above are shown in millimetres

The above list is for ASME B16.5, MSS-SP44 and ASME B16.47 series A flanges only. Other flanges or connections are available on request.

Goodwin Axial Choke Valves can be used as an alternative to:

- Angle Choke Valves
- Rotating Disc Choke Valves
- Conventional Globe Control Valves

www.goodwinflowcontrol.com

