



Axial Control Valves Weights CB / CU Series

ASME B16.5

SIZE	ASME PRESSURE RATING					
	150	300	600	900	1500	2500
2"	34	36	44	97	97	169
3"	77	83	102	127	204	345
4"	126	134	181	214	318	561
6"	147	186	322	413	697	1,370
8"	255	325	626	838	1,226	2,198
10"	396	545	1,177	1,416	2,268	3,840
12"	611	798	1,503	2,039	1820	3,035
14"	662	770	1,098	1,299	2,495	-
16"	897	1,064	1,640	1,867	3,430	-
18"	1,116	1,268	2,110	2,393	4,340	-
20"	1,450	1,646	2,768	3,214	5,501	-
24"	2,319	2,626	3,535	5,054	9,439	-
28"	3,422	3,905	5,206	7,178	-	-
30"	3,918	4,460	6,276	8,575	-	-
32"	4,475	5,141	7,554	10,423	-	-
36"	5,082	6,402	10,629	13,903	-	-
40"	8,221	8,512	14,065	18,334	-	-
42"	8,406	8,744	14,891	19,075	-	-
48"	11,574	12,814	24,395	29,926	-	-

All above weights are shown in Kgs (Bare Stem)

www.goodwinvalves.com



AXIAL ISOLATION & CONTROL VALVES

Hydrogen Ready

FET : ISO 15848 RATE A CLASS (HS)